



Screeed Preparation Products

PATCHiTe®

Rapid setting patching compound.

VAPORiTe® +PLUS

Water based epoxy moisture barrier.

BONDiTe®

Rapid-drying high strength primer.

iTe SLURRY®

Keying Promoter.

LEVELiTe® F10

Self-Levelling compound for residential and light commercial use.

LEVELiTe® F30

Self-Levelling compound for high performance vinyl sheeting.

LEVELiTe® FX

Express, Rapid Set self-levelling floor screed compound.

LEVELiTe® F50

Self-Levelling compound super strength industrial applications.

LEVELiTe® F100

Self-Levelling compound super strength industrial applications.



PHYSICAL 7 Clarke Street South, Alrode, Alberton, 1457, South Africa
POSTAL P.O. Box 17224, Randhart, 1457, South Africa
TEL +27 (0)11 864 4918
FAX +27 (0)11 864 2123

info@iteproducts.co.za
www.iteproducts.co.za

Endorsed by:

Belgotex®



April 2021



PATCHiTe®

A rapid cement based compound which dries in approx. 20 minutes. It is used for filling deep or large holes or depressions in screeds prior to the application of self-levellers.

- Sets very hard, very fast
- Shrinkage compensated
- 30 Minute working time
- Trafficable in less than 1 hour
- Usage 2Kg per m² per 1mm thickness
- Bag Size 25Kg



LEVELiTe® FX

An Express, Rapid Set self-levelling floor screed compound developed for a wide range of applications including residential, commercial and light industrial applications that sets to 25MPa. Specifically formulated to enable same-day installation of floor coverings.

- can be walked on within an hour
- Sets to 25 Mpa after 28 days
- Resistant to moisture once cured
- Will not swell or delaminate



BONDiTe®

Is used as a primer before the application of LEVELiTe self-levellers. It is fast drying and will not re-emulsify once dry. It prevents air bubbles in the LEVELiTe, acts as a flow promoter and binds dusty screeds.

- Dries rapidly
- Available in 5Litre and 25Litre containers
- Usage Rate 4m²/Litre



LEVELiTe® F10

Entry level self-levelling compound designed for use in residential and light commercial applications where wood laminate, click system LVT and stick down LVT's, as well as carpets, are to be installed. Not recommended for castor traffic.

- Classed as P2 Self-Levelling Underlayment - EN13813
- Sets to 18 MPa
- Shrinkage <0,2%
- 30 Minute working time
- Trafficable after 2 hours
- Usage 1,7Kg per m² per 1mm thickness
- Bag Size 24Kg (+/- 4,7m² coverage @ 3mm)



LEVELiTe® F50

High performance, impact resistant self-levelling compound designed for use in industrial applications where industrial grade floor coverings or epoxy coatings are to be installed or applied.

- Classed as P4R Self-Levelling Underlayment - EN13813
- Sets to 35 MPa
- Shrinkage <0,2%
- 30 Minute working time
- Trafficable after 2 hours
- Usage 1,6Kg per m² per 1mm thickness
- Bag Size 24Kg (+/- 4,3m² coverage @ 3mm)



VAPORiTe® +PLUS

2 Part water based epoxy moisture and vapour barrier which prevents screed moisture from affecting the adhesive or resilient floor covering after installation. VAPORiTe +PLUS is applied in 2 coats, which after completely drying, is coated with iTe SLURRY to promote adhesion between the LEVELiTe and VAPORiTe +PLUS.

- Water based- no VOC's
- Sets at 2 hours per coat
- Coverage at +/- 20m² per 4,5Kg pack
- Odour free
- 4,5Kg Pack comprising 3,5Kg Base and 1Kg activator
- 4 Minute mixing with electric stirrer



LEVELiTe® F30

High performance self-levelling compound used in health care, commercial and light industrial applications such as Vinyl sheeting, tiles, LVT's etc.

- Classed as P3 Self-Levelling Underlayment - EN13813
- Sets to 25 MPa
- Shrinkage <0,2%
- 35 Minute working time
- Trafficable after 2 hours
- Usage 1,5Kg per m² per 1mm thickness
- Bag Size 21,5Kg (+/- 4,8m² coverage @ 3mm)



LEVELiTe® F100

This rapid setting micro finish self-leveller can be applied in extremely thin applications to eliminate minor surface imperfections or to create ramps for transitions prior to the installation of vinyl flooring which is surface sensitive.

- Sets to 45 MPa
- Shrinkage <0,15%
- 30 Minute working time
- Trafficable after 1 hour
- Usage 1,5Kg per m² per 1mm thickness
- Bag Size 17Kg (+/- 11m² coverage @ 1mm)



iTe SLURRY®

iTe SLURRY is a premixed slurry to promote bonding between epoxy coatings, ceramic or porcelain tiles, very tight closed surfaces and LEVELiTe self-levelling compound. Very high bonding characteristics

- Rapid drying
- Odour free
- No VOC's
- 15 and 30Kg Buckets covering between 80 and 100m² for the 15Kg pack, double that for the 30Kg pack